

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/16/2022

Reviewed on 08/16/2022

## 1 Identification

- **Product identifier**
- **Trade name:** EasyFill
- **Article number:** 11039-250
- **Application of the substance / the mixture** Filler and surfacer
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Loba Wakol LLC  
2732 Hwy 74 West  
Wadesboro, NC 28170  
Phone: (800) 230-6456  
Email: info@loba-wakol.com
- **Emergency telephone number:**  
Emergency CONTACT (24-Hour-Number)  
GBK/Infotrac ID 112404 : (USA domestic) 1 800 535 5053

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  
The product is not classified, according to the Globally Harmonized System (GHS).
- **Label elements**
- **GHS label elements** Void
- **Hazard pictograms** Void
- **Signal word** Void
- **Hazard statements** Void
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	0	Health = 0
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

## 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.
- **Dangerous components:**  
The mixture contains softwood dust, which is marked with H 351. However, the danger only arises if the material is present as dust. However, since this is not the case in the present mixture, this classification is irrelevant and is not used to classify the mixture. For activities in which the softwood dust could be released from the named product (e.g. grinding), the applicable national occupational exposure limit values must be observed.

CAS: 34590-94-8	Dipropylene glycol monomethyl ether	2.5-5%
EINECS: 252-104-2	Flammable Liquids 4, H227	

(Contd. on page 2)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/16/2022

Reviewed on 08/16/2022

Trade name: EasyFill

(Contd. of page 1)

CAS: 9004-34-6 EINECS: 232-674-9	Cellulose (dust) ☠ Carcinogenicity 2, H351	<2.5%
EC number: 939-704-6	Tetrasodium-N-(1,2-dicarboxyethyl)-N-octadecyl sulfosuccinamate ⚠ Eye Irritation 2A, H319	<2.5%
CAS: 75-28-5 EINECS: 200-857-2	isobutane ⚠ Flammable Gases 1, H220; ⚠ Gases under Pressure - Compressed gas, H280	<2.5%
CAS: 67-56-1 EINECS: 200-659-6	methanol ⚠ Flammable Liquids 2, H225; ☠ Acute Toxicity - Oral 3, H301; Acute Toxicity - Dermal 3, H311; Acute Toxicity - Inhalation 3, H331; ☠ Specific Target Organ Toxicity - Single Exposure 1, H370	<0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## 4 First-aid measures

- **Description of first aid measures**
- **General information:** No special measures required.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Dilute with plenty of water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

34590-94-8	Dipropylene glycol monomethyl ether	150 ppm
75-28-5	isobutane	5500* ppm
112945-52-5	artificial silica	18 mg/m <sup>3</sup>
63148-62-9	Polydimethylsiloxane	65 mg/m <sup>3</sup>

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/16/2022

Reviewed on 08/16/2022

**Trade name: EasyFill**

(Contd. of page 2)

67-68-5	dimethyl sulfoxide	150 ppm
67-56-1	methanol	530 ppm
1336-21-6	ammonia, aqueous solution	61 ppm
7447-41-8	lithium chloride	2.3 mg/m <sup>3</sup>
1309-37-1	Pigment Red 101	15 mg/m <sup>3</sup>
25322-68-3	Poly-(oxy-1,2-ethanediyl), $\alpha$ -hydro- $\omega$ -hydroxy- Ethane-1,2-diol, ethoxylated	30 mg/m <sup>3</sup>
107-22-2	Oxalaldehyde	0.3 mg/m <sup>3</sup>
55406-53-6	3-Iodo-2-propynylbutylcarbamate	3.3 mg/m <sup>3</sup>
556-67-2	octamethylcyclotetrasiloxane	30 ppm

**· PAC-2:**

34590-94-8	Dipropylene glycol monomethyl ether	1700* ppm
75-28-5	isobutane	17000** ppm
112945-52-5	artificial silica	100 mg/m <sup>3</sup>
63148-62-9	Polydimethylsiloxane	720 mg/m <sup>3</sup>
67-68-5	dimethyl sulfoxide	290 ppm
67-56-1	methanol	2,100 ppm
1336-21-6	ammonia, aqueous solution	330 ppm
7447-41-8	lithium chloride	25 mg/m <sup>3</sup>
1309-37-1	Pigment Red 101	360 mg/m <sup>3</sup>
25322-68-3	Poly-(oxy-1,2-ethanediyl), $\alpha$ -hydro- $\omega$ -hydroxy- Ethane-1,2-diol, ethoxylated	1,300 mg/m <sup>3</sup>
107-22-2	Oxalaldehyde	46 mg/m <sup>3</sup>
55406-53-6	3-Iodo-2-propynylbutylcarbamate	36 mg/m <sup>3</sup>
556-67-2	octamethylcyclotetrasiloxane	68 ppm

**· PAC-3:**

34590-94-8	Dipropylene glycol monomethyl ether	9900** ppm
75-28-5	isobutane	53000*** ppm
112945-52-5	artificial silica	630 mg/m <sup>3</sup>
63148-62-9	Polydimethylsiloxane	4,300 mg/m <sup>3</sup>
67-68-5	dimethyl sulfoxide	1,800 ppm
67-56-1	methanol	7200* ppm
1336-21-6	ammonia, aqueous solution	2,300 ppm
7447-41-8	lithium chloride	150 mg/m <sup>3</sup>
1309-37-1	Pigment Red 101	2,200 mg/m <sup>3</sup>
25322-68-3	Poly-(oxy-1,2-ethanediyl), $\alpha$ -hydro- $\omega$ -hydroxy- Ethane-1,2-diol, ethoxylated	7,700 mg/m <sup>3</sup>
107-22-2	Oxalaldehyde	280 mg/m <sup>3</sup>
55406-53-6	3-Iodo-2-propynylbutylcarbamate	220 mg/m <sup>3</sup>
556-67-2	octamethylcyclotetrasiloxane	130 ppm

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special measures required.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 4)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/16/2022

Reviewed on 08/16/2022

Trade name: EasyFill

(Contd. of page 3)

- **Further information about storage conditions:** None.
- **Storage class:** 12
- **Specific end use(s)** No further relevant information available.

## \* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

### 34590-94-8 Dipropylene glycol monomethyl ether

PEL	Long-term value: 600 mg/m <sup>3</sup> , 100 ppm Skin
REL	Short-term value: 900 mg/m <sup>3</sup> , 150 ppm Long-term value: 600 mg/m <sup>3</sup> , 100 ppm Skin
TLV	Long-term value: NIC-50 ppm (Skin)

### 9004-34-6 Cellulose (dust)

PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m <sup>3</sup> *total dust **respirable fraction
TLV	Long-term value: 10 mg/m <sup>3</sup>

### 75-28-5 isobutane

TLV	Short-term value: 1000 ppm (EX)
-----	------------------------------------

### 67-56-1 methanol

PEL	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
REL	Short-term value: 325 mg/m <sup>3</sup> , 250 ppm Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin
TLV	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI

- **Ingredients with biological limit values:**

### 67-56-1 methanol

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
The usual precautionary measures for handling chemicals should be followed.
- **Breathing equipment:** Not required.
- **Protection of hands:**  
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/16/2022

Reviewed on 08/16/2022

Trade name: EasyFill

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material:  $\geq 0.4$  mm

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

Value for the permeation: Level  $\leq 6$

- **Eye protection:** Goggles recommended during refilling.

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

<b>Form:</b>	Fluid
<b>Color:</b>	Whitish
<b>Odor:</b>	Recognizable
<b>Odor threshold:</b>	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

<b>Melting point/Melting range:</b>	Undetermined.
<b>Boiling point/Boiling range:</b>	100 °C (212 °F)

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Lower:** Not determined.

- **Upper:** Not determined.

- **Vapor pressure:** Not determined.

- **Density at 20 °C (68 °F):** 0.84 g/cm<sup>3</sup> (7.0098 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

**Water:** Fully miscible.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

<b>Dynamic at 20 °C (68 °F):</b>	350 mPas
<b>Kinematic:</b>	Not determined.

- **Solids content:** 30.0 %

(Contd. on page 6)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/16/2022

Reviewed on 08/16/2022

Trade name: EasyFill

(Contd. of page 5)

· **Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**34590-94-8 Dipropylene glycol monomethyl ether**

Oral LD50 5,135 mg/kg (rat)

Dermal LD50 9,500 mg/kg (rat)

**Tetrasodium-N-(1,2-dicarboxyethyl)-N-octadecyl sulfosuccinamate**

Oral LD50 6,500 mg/kg (rat)

Dermal LD50 3,500 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product is not subject to classification according to internally approved calculation methods for preparations:  
When used and handled according to specifications, the product does not have any harmful effects according to our experience and the information provided to us.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

9003-55-8 Benzene, ethenyl-, polymer with 1,3-butadiene

3

1309-37-1 Pigment Red 101

3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/16/2022

Reviewed on 08/16/2022

Trade name: EasyFill

(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
After prior treatment product has to be landfilled or incinerated adhering to the regulations pertaining to the disposal of especially hazardous waste.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- |   |                 |
|---|-----------------|
| · <b>UN-Number</b>  |                 |
| · <b>DOT, ADR, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>UN proper shipping name</b>  |                 |
| · <b>DOT, ADR, ADN, IMDG, IATA</b>  | not regulated   |
| · <b>Transport hazard class(es)</b>   |                 |
| · <b>DOT, ADR, ADN, IMDG, IATA</b>  |                 |
| · <b>Class</b>  | not regulated   |
| · <b>Packing group</b>  |                 |
| · <b>DOT, ADR, IMDG, IATA</b>   | not regulated   |
| · <b>Environmental hazards:</b>   | Not applicable. |
| · <b>Special precautions for user</b>   | Not applicable. |
| · <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b> | Not applicable. |
| · <b>UN "Model Regulation":</b>   | not regulated   |

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **TSCA (Toxic Substances Control Act):** All components are on the TSCA inventory

### · **Hazardous Air Pollutants**

67-56-1 | methanol

### · **Proposition 65**

#### · **Chemicals known to cause cancer:**

None of the ingredients is listed.

#### · **Chemicals known to cause reproductive toxicity for females:**

67-56-1 | methanol

(Contd. on page 8)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 08/16/2022

Reviewed on 08/16/2022

Trade name: EasyFill

(Contd. of page 7)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **GHS label elements** Void

· **Hazard pictograms** Void

· **Signal word** Void

· **Hazard statements** Void

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapor.

H227 Combustible liquid.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H351 Suspected of causing cancer.

H370 Causes damage to organs.

· **Department issuing SDS:** Productmanagement.

· **Contact:**

· **Date of preparation / last revision** 08/16/2022 / 20

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Gases 1: Flammable gases – Category 1

Gases under Pressure - Compressed gas: Gases under pressure – Compressed gas

Flammable Liquids 2: Flammable liquids – Category 2

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity - Oral 3: Acute toxicity – Category 3

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) – Category 1

· **\* Data compared to the previous version altered.**



# Sicherheitsdatenblatt

## gemäß 1907/2006/EG, Artikel 31

Druckdatum: 16.08.2022

Versionsnummer 21

überarbeitet am: 16.08.2022

### 1 Bezeichnung des Stoffs beziehungsweise des Gemisches und des Unternehmens

- **Produktidentifikator**
- **Handelsname:** EasyFill
- **Artikelnummer:** 11039-250
- **Verwendung des Stoffs / des Gemisches** Füller und Spachtel
- **Einzelheiten zum Lieferanten, der das Sicherheitsdatenblatt bereitstellt**
- **Hersteller/Lieferant:**  
Loba Wakol LLC  
2732 Hwy 74 West  
Wadesboro, NC 28170  
Phone: (800) 230-6456  
Email: [info@loba-wakol.com](mailto:info@loba-wakol.com)
- **Notrufnummer:**  
Emergency CONTACT (24-Hour-Number)  
GBK/Infotrac ID 112404 : (USA domestic) 1 800 535 5053

### 2 Mögliche Gefahren

- **Einstufung des Stoffs oder Gemisches**  
Das Produkt ist gemäß GHS (Globally Harmonized System) nicht eingestuft.
- **Kennzeichnungselemente**
- **GHS-Kennzeichnungselemente** entfällt
- **Gefahrenpiktogramme** entfällt
- **Signalwort** entfällt
- **Gefahrenhinweise** entfällt
- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**



- **Sonstige Gefahren**
- **Ergebnisse der PBT- und vPvB-Beurteilung**
- **PBT:** Nicht anwendbar.
- **vPvB:** Nicht anwendbar.

### 3 Zusammensetzung/Angaben zu Bestandteilen

- **Chemische Charakterisierung: Gemische**
- **Beschreibung:** Gemisch aus nachfolgend angeführten Stoffen mit ungefährlichen Beimengungen.
- **Gefährliche Inhaltsstoffe:**  
Das Gemisch enthält Weichholzstaub, welcher mit H 351 gekennzeichnet ist. Die Gefahr entsteht jedoch nur, sofern das Material als Staub vorliegt. Da dies in dem vorliegenden Gemisch jedoch nicht der Fall ist, ist diese Einstufung irrelevant und wird nicht zur Einstufung des Gemisches herangezogen. Bei Tätigkeiten, bei denen der Weichholzstaub aus dem genannten Produkt freigesetzt werden könnte (z. B. Abschleifen), sind die jeweils gültigen nationalen Arbeitsplatzgrenzwerte einzuhalten.

CAS: 34590-94-8	Dipropylenglykolmonomethylether	2,5-5%
EINECS: 252-104-2	Entz. Fl. 4, H227	

(Fortsetzung auf Seite 2)

# Sicherheitsdatenblatt

## gemäß 1907/2006/EG, Artikel 31

Druckdatum: 16.08.2022

Versionsnummer 21

überarbeitet am: 16.08.2022

**Handelsname: EasyFill**

(Fortsetzung von Seite 1)

CAS: 9004-34-6 EINECS: 232-674-9	Cellulose (Staub) ☠ Karz. 2, H351	≥0,1-<2,5%
EG-Nummer: 939-704-6	Tetranatrium-N-(1,2-dicarboxyethyl)-N-octadecylsulfosuccinat ⚠ Eye Irritation 2A, H319	<2,5%
CAS: 75-28-5 EINECS: 200-857-2 Indexnummer: 601-004-00-0	Isobutan ⚠ Entz. Gas 1, H220; ⚠ Pressgas, H280	<2,5%
CAS: 2634-33-5 EINECS: 220-120-9 Indexnummer: 613-088-00-6	1,2-Benzisothiazol-3(2H)-on ⚠ Augenschäd. 1, H318; ⚠ Akut Tox. 4, H302; Hautreiz. 2, H315; Sens. Haut 1, H317	≤0,01%
CAS: 55965-84-9 EG-Nummer: 911-418-6 Indexnummer: 613-167-00-5	Gemisch aus: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG nr. 220-239-6] (3:1) ⚠ Akut Tox. 3, H301; Akut Tox. 2, H310; Akut Tox. 2, H330; ⚠ Hautätz. 1C, H314; Augenschäd. 1, H318; ⚠ Sens. Haut 1A, H317	≥0,00025-<0,0015%

· **Additional information:** Der Wortlaut der angeführten Gefahrenhinweise ist dem Abschnitt 16 zu entnehmen.

### 4 Erste-Hilfe-Maßnahmen

- **Beschreibung der Erste-Hilfe-Maßnahmen**
- **Allgemeine Hinweise:** Keine besonderen Maßnahmen erforderlich.
- **nach Einatmen:** Frischluftzufuhr, bei Beschwerden Arzt aufsuchen.
- **nach Hautkontakt:** Im allgemeinen ist das Produkt nicht hautreizend.
- **nach Augenkontakt:** Augen bei geöffnetem Lidspalt mehrere Minuten mit fließendem Wasser spülen.
- **nach Verschlucken:** Bei anhaltenden Beschwerden Arzt konsultieren.
- **Hinweise für den Arzt:**
- **Wichtigste akute und verzögert auftretende Symptome und Wirkungen**  
Keine weiteren relevanten Informationen verfügbar.
- **Hinweise auf ärztliche Soforthilfe oder Spezialbehandlung**  
Keine weiteren relevanten Informationen verfügbar.

### 5 Maßnahmen zur Brandbekämpfung

- **Löschmittel**
- **Geeignete Löschmittel:** Feuerlöschmaßnahmen auf die Umgebung abstimmen.
- **Besondere vom Stoff oder Gemisch ausgehende Gefahren**  
Keine weiteren relevanten Informationen verfügbar.
- **Hinweise für die Brandbekämpfung**
- **Besondere Schutzausrüstung:** Keine besonderen Maßnahmen erforderlich.

### 6 Maßnahmen bei unbeabsichtigter Freisetzung

- **Personenbezogene Vorsichtsmaßnahmen, Schutzausrüstungen und in Notfällen anzuwendende Verfahren**  
Nicht erforderlich.
- **Umweltschutzmaßnahmen:**  
Nicht in die Kanalisation oder in Gewässer gelangen lassen.  
Bei Eindringen in Gewässer oder Kanalisation zuständige Behörden benachrichtigen.  
Mit viel Wasser verdünnen.
- **Methoden und Material für Rückhaltung und Reinigung:**  
Mit flüssigkeitsbindendem Material (Sand, Kieselgur, Säurebinder, Universalbinder, Sägemehl) aufnehmen.
- **Verweis auf andere Abschnitte**  
Informationen zur sicheren Handhabung siehe Abschnitt 7.

(Fortsetzung auf Seite 3)

# Sicherheitsdatenblatt

## gemäß 1907/2006/EG, Artikel 31

Druckdatum: 16.08.2022

Versionsnummer 21

überarbeitet am: 16.08.2022

**Handelsname: EasyFill**

(Fortsetzung von Seite 2)

Informationen zur persönlichen Schutzausrüstung siehe Abschnitt 8.

Informationen zur Entsorgung siehe Abschnitt 13.

**· Protective Action Criteria for Chemicals****· PAC-1:**

34590-94-8	Dipropylenglykolmonomethylether	150 ppm
75-28-5	Isobutan	5500* ppm
112945-52-5	Siliziumdioxid	18 mg/m <sup>3</sup>
63148-62-9	Polydimethylsiloxan	65 mg/m <sup>3</sup>
67-68-5	Dimethylsulfoxid	150 ppm
67-56-1	Methanol	530 ppm
1336-21-6	Ammoniaklösung	61 ppm
7447-41-8	Lithiumchlorid	2.3 mg/m <sup>3</sup>
1309-37-1	Pigment Red 101	15 mg/m <sup>3</sup>
25322-68-3	Poly-(oxy-1,2-ethandiyl), $\alpha$ -hydro- $\omega$ -hydroxy-ethan-1,2-diol, ethoxyliert	30 mg/m <sup>3</sup>
107-22-2	Oxalaldehyd	0.3 mg/m <sup>3</sup>
55406-53-6	3-Iod-2-propinylbutylcarbammat	3.3 mg/m <sup>3</sup>
556-67-2	Octamethylcyclotetrasiloxan	30 ppm

**· PAC-2:**

34590-94-8	Dipropylenglykolmonomethylether	1700* ppm
75-28-5	Isobutan	17000** ppm
112945-52-5	Siliziumdioxid	100 mg/m <sup>3</sup>
63148-62-9	Polydimethylsiloxan	720 mg/m <sup>3</sup>
67-68-5	Dimethylsulfoxid	290 ppm
67-56-1	Methanol	2,100 ppm
1336-21-6	Ammoniaklösung	330 ppm
7447-41-8	Lithiumchlorid	25 mg/m <sup>3</sup>
1309-37-1	Pigment Red 101	360 mg/m <sup>3</sup>
25322-68-3	Poly-(oxy-1,2-ethandiyl), $\alpha$ -hydro- $\omega$ -hydroxy-ethan-1,2-diol, ethoxyliert	1,300 mg/m <sup>3</sup>
107-22-2	Oxalaldehyd	46 mg/m <sup>3</sup>
55406-53-6	3-Iod-2-propinylbutylcarbammat	36 mg/m <sup>3</sup>
556-67-2	Octamethylcyclotetrasiloxan	68 ppm

**· PAC-3:**

34590-94-8	Dipropylenglykolmonomethylether	9900** ppm
75-28-5	Isobutan	53000*** ppm
112945-52-5	Siliziumdioxid	630 mg/m <sup>3</sup>
63148-62-9	Polydimethylsiloxan	4,300 mg/m <sup>3</sup>
67-68-5	Dimethylsulfoxid	1,800 ppm
67-56-1	Methanol	7200* ppm
1336-21-6	Ammoniaklösung	2,300 ppm
7447-41-8	Lithiumchlorid	150 mg/m <sup>3</sup>
1309-37-1	Pigment Red 101	2,200 mg/m <sup>3</sup>
25322-68-3	Poly-(oxy-1,2-ethandiyl), $\alpha$ -hydro- $\omega$ -hydroxy-ethan-1,2-diol, ethoxyliert	7,700 mg/m <sup>3</sup>
107-22-2	Oxalaldehyd	280 mg/m <sup>3</sup>
55406-53-6	3-Iod-2-propinylbutylcarbammat	220 mg/m <sup>3</sup>
556-67-2	Octamethylcyclotetrasiloxan	130 ppm

DE

(Fortsetzung auf Seite 4)

# Sicherheitsdatenblatt

## gemäß 1907/2006/EG, Artikel 31

Druckdatum: 16.08.2022

Versionsnummer 21

überarbeitet am: 16.08.2022

Handelsname: EasyFill

(Fortsetzung von Seite 3)

### 7 Handhabung und Lagerung

- **Handhabung:**
- **Schutzmaßnahmen zur sicheren Handhabung:** Keine besonderen Maßnahmen erforderlich.
- **Hinweise zum Brand- und Explosionsschutz:** Keine besonderen Maßnahmen erforderlich.
- **Bedingungen zur sicheren Lagerung unter Berücksichtigung von Unverträglichkeiten**
- **Lagerung:**
- **Anforderung an Lagerräume und Behälter:** Keine besonderen Anforderungen.
- **Zusammenlagerungshinweise:** nicht erforderlich
- **Weitere Angaben zu den Lagerbedingungen:** keine
- **Lagerklasse:** 12
- **Spezifische Endanwendungen:** Keine weiteren relevanten Informationen verfügbar.

### 8 Begrenzung und Überwachung der Exposition/Persönliche Schutzausrüstungen

- **Zusätzliche Hinweise zur Gestaltung technischer Anlagen:** Keine weiteren Angaben, siehe Abschnitt 7.
- **Zu überwachende Parameter**
- **Bestandteile mit arbeitsplatzbezogenen, zu überwachenden Grenzwerten:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

#### 34590-94-8 Dipropylenglykolmonomethylether

AGW	Langzeitwert: 310 mg/m <sup>3</sup> , 50 ml/m <sup>3</sup> 1(I);DFG, EU, 11
-----	--

#### 75-28-5 Isobutan

AGW	Langzeitwert: 2400 mg/m <sup>3</sup> , 1000 ml/m <sup>3</sup> 4(II);DFG
-----	--

#### 2634-33-5 1,2-Benzisothiazol-3(2H)-on

MAK	vgl.Abschn.IIb und Xc
-----	-----------------------

#### 55965-84-9 Gemisch aus: 5-Chlor-2-methyl-2H-isothiazol-3-on [EG nr. 247-500-7] und 2-Methyl-2H-isothiazol-3-on [EG nr. 220-239-6] (3:1)

MAK	Langzeitwert: 0,2E mg/m <sup>3</sup> vgl.Abschn.Xc
-----	---

- **Bestandteile mit biologischen Grenzwerten:**

#### 67-56-1 Methanol

BEI	15 mg/L Medium: urine Time: end of shift Parameter: Methanol (background, nonspecific)
-----	---

- **Zusätzliche Hinweise:** Als Grundlage dienen die bei der Erstellung gültigen Listen.
- **Begrenzung und Überwachung der Exposition**
- **Persönliche Schutzausrüstung:**
- **Allgemeine Schutz- und Hygienemaßnahmen:**  
Die üblichen Vorsichtsmaßnahmen beim Umgang mit Chemikalien sind zu beachten.
- **Atemschutz:** nicht erforderlich.
- **Handschutz:**  
Das Handschuhmaterial muss undurchlässig und beständig gegen das Produkt / den Stoff / die Zubereitung sein.  
Auswahl des Handschuhmaterials unter Beachtung der Durchbruchzeiten, Permeationsraten und der Degradation.
- **Handschuhmaterial**  
Nitrilkautschuk  
Die Auswahl eines geeigneten Handschuhs ist nicht nur vom Material, sondern auch von weiteren Qualitätsmerkmalen abhängig und von Hersteller zu Hersteller unterschiedlich. Da das Produkt eine

(Fortsetzung auf Seite 5)

# Sicherheitsdatenblatt

## gemäß 1907/2006/EG, Artikel 31

Druckdatum: 16.08.2022

Versionsnummer 21

überarbeitet am: 16.08.2022

**Handelsname: EasyFill**

(Fortsetzung von Seite 4)

Zubereitung aus mehreren Stoffen darstellt, ist die Beständigkeit von Handschuhmaterialien nicht vorausberechenbar und muß deshalb vor dem Einsatz überprüft werden.

Empfohlene Materialstärke:  $\geq 0,4$  mm

· **Durchdringungszeit des Handschuhmaterials**

Die genaue Durchbruchzeit ist beim Schutzhandschuhhersteller zu erfahren und einzuhalten.

Für das Gemisch nachfolgend genannter Chemikalien muss die Durchbruchzeit mindestens 480 Minuten (Permeation gemäß EN 374 Teil 3: Level 6) betragen.

Wert für die Permeation: Level 6

· **Augenschutz:** Beim Umfüllen Schutzbrille empfehlenswert.

## 9 Physikalische und chemische Eigenschaften

· **Angaben zu den grundlegenden physikalischen und chemischen Eigenschaften**

· **Allgemeine Angaben**

· **Aussehen:**

<b>Form:</b>	flüssig
<b>Farbe:</b>	weißlich
<b>Geruch:</b>	wahrnehmbar
<b>Geruchsschwelle:</b>	Nicht bestimmt.

· **pH-Wert:** Nicht bestimmt.

· **Zustandsänderung**

<b>Schmelzpunkt/Gefrierpunkt:</b>	Nicht bestimmt
<b>Siedebeginn und Siedebereich:</b>	100 °C

· **Flammpunkt:** Nicht anwendbar

· **Entzündbarkeit (fest, gasförmig):** Nicht anwendbar.

· **Zersetzungstemperatur:** Nicht bestimmt.

· **Selbstentzündungstemperatur:** Das Produkt ist nicht selbstentzündlich.

· **Explosive Eigenschaften:** Das Produkt ist nicht explosionsgefährlich.

<b>untere:</b>	Nicht bestimmt.
<b>obere:</b>	Nicht bestimmt.

· **Dampfdruck:** Nicht bestimmt.

<b>Dichte bei 20 °C:</b>	0,84 g/cm <sup>3</sup>
<b>Relative Dichte</b>	Nicht bestimmt.
<b>Dampfdichte</b>	Nicht bestimmt.
<b>Verdampfungsgeschwindigkeit</b>	Nicht bestimmt.

· **Löslichkeit in / Mischbarkeit mit Wasser:** vollständig mischbar

· **Verteilungskoeffizient: n-Octanol/Wasser:** Nicht bestimmt.

<b>Viskosität:</b>	
<b>dynamisch bei 20 °C:</b>	350 mPas
<b>kinematisch:</b>	Nicht bestimmt.

**Festkörpergehalt:** 30,0 %

· **Sonstige Angaben** Keine weiteren relevanten Informationen verfügbar.

## 10 Stabilität und Reaktivität

· **Reaktivität** Keine weiteren relevanten Informationen verfügbar.

(Fortsetzung auf Seite 6)

# Sicherheitsdatenblatt

## gemäß 1907/2006/EG, Artikel 31

Druckdatum: 16.08.2022

Versionsnummer 21

überarbeitet am: 16.08.2022

**Handelsname: EasyFill**

(Fortsetzung von Seite 5)

- **Chemische Stabilität**
- **Thermische Zersetzung / zu vermeidende Bedingungen:**  
Keine Zersetzung bei bestimmungsgemäßer Verwendung.
- **Möglichkeit gefährlicher Reaktionen** Keine gefährlichen Reaktionen bekannt.
- **Zu vermeidende Bedingungen** Keine weiteren relevanten Informationen verfügbar.
- **Unverträgliche Materialien:** Keine weiteren relevanten Informationen verfügbar.
- **Gefährliche Zersetzungsprodukte:** keine gefährlichen Zersetzungsprodukte bekannt.

## 11 Toxikologische Angaben

- **Angaben zu toxikologischen Wirkungen**
- **Akute Toxizität**

- **Einstufungsrelevante LD/LC50-Werte:**

### 34590-94-8 Dipropylenglykolmonomethylether

Oral LD50 5.135 mg/kg (Ratte)

Dermal LD50 9.500 mg/kg (Ratte)

### Tetranatrium-N-(1,2-dicarboxyethyl)-N-octadecylsulfosuccinat

Oral LD50 6.500 mg/kg (Ratte)

Dermal LD50 3.500 mg/kg (Ratte)

- **Primäre Reizwirkung:**
- **Ätz-/Reizwirkung auf die Haut** Keine Reizwirkung
- **Schwere Augenschädigung/-reizung** Keine Reizwirkung
- **Sensibilisierung der Atemwege/Haut** keine sensibilisierende Wirkung bekannt
- **Zusätzliche toxikologische Hinweise:**

Das Produkt ist nicht kennzeichnungspflichtig aufgrund des Berechnungsverfahrens der Allgemeinen Einstufungsrichtlinie für Zubereitungen der EG in der letztgültigen Fassung.

Bei sachgemäßem Umgang und bestimmungsgemäßer Verwendung verursacht das Produkt nach unseren Erfahrungen und den uns vorliegenden Informationen keine gesundheitsschädlichen Wirkungen.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

9003-55-8 Styrol-Butadien-Copolymer

3

1309-37-1 Pigment Red 101

3

- **NTP (National Toxicology Program)**

Keiner der Inhaltsstoffe ist enthalten.

- **OSHA (Occupational Safety & Health Administration)**

Keiner der Inhaltsstoffe ist enthalten.

## 12 Umweltbezogene Angaben

- **Toxizität**
- **Aquatische Toxizität:** Keine weiteren relevanten Informationen verfügbar.
- **Persistenz und Abbaubarkeit** Keine weiteren relevanten Informationen verfügbar.
- **Verhalten in Umweltkompartimenten:**
- **Bioakkumulationspotenzial** Keine weiteren relevanten Informationen verfügbar.
- **Mobilität im Boden** Keine weiteren relevanten Informationen verfügbar.
- **Weitere ökologische Hinweise:**
- **Allgemeine Hinweise:**  
Wassergefährdungsklasse 1 (Selbsteinstufung): schwach wassergefährdend  
Nicht in das Grundwasser, in Gewässer oder in die Kanalisation gelangen lassen.
- **Ergebnisse der PBT- und vPvB-Beurteilung**
- **PBT:** Nicht anwendbar.
- **vPvB:** Nicht anwendbar.

(Fortsetzung auf Seite 7)



# Sicherheitsdatenblatt

## gemäß 1907/2006/EG, Artikel 31

Druckdatum: 16.08.2022

Versionsnummer 21

überarbeitet am: 16.08.2022

**Handelsname: EasyFill**

(Fortsetzung von Seite 6)

· **Andere schädliche Wirkungen** Keine weiteren relevanten Informationen verfügbar.

### 13 Hinweise zur Entsorgung

- **Verfahren der Abfallbehandlung**
- **Empfehlung:**  
Muß unter Beachtung der Sonderabfallvorschriften nach Vorbehandlung einer hierfür zugelassenen Sonderabfalldeponie oder Sonderabfallverbrennungsanlage zugeführt werden.
- **Ungereinigte Verpackungen:**
- **Empfehlung:** Entsorgung gemäß den behördlichen Vorschriften.
- **Empfohlenes Reinigungsmittel:** Wasser, gegebenenfalls mit Zusatz von Reinigungsmitteln.

### 14 Angaben zum Transport

- |  |                  |
|--|------------------|
| · <b>UN-Nummer</b>   |                  |
| · <b>DOT, ADR, ADN, IMDG, IATA</b>   | entfällt         |
| · <b>Ordnungsgemäße UN-Versandbezeichnung</b>  |                  |
| · <b>DOT, ADR, ADN, IMDG, IATA</b>   | entfällt         |
| · <b>Transportgefahrenklassen</b>  |                  |
| · <b>DOT, ADR, ADN, IMDG, IATA</b>   |                  |
| · <b>Class</b>   | entfällt         |
| · <b>Verpackungsgruppe</b>   |                  |
| · <b>DOT, ADR, IMDG, IATA</b>  | entfällt         |
| · <b>Umweltgefahren:</b>   | Nicht anwendbar. |
| · <b>Besondere Vorsichtsmaßnahmen für den Verwender</b>                                    | Nicht anwendbar. |
| · <b>Massengutbeförderung gemäß Anhang II des MARPOL-Übereinkommens und gemäß IBC-Code</b> | Nicht anwendbar. |
| · <b>UN "Model Regulation":</b>  | entfällt         |

### 15 Rechtsvorschriften

- **Vorschriften zu Sicherheit, Gesundheits- und Umweltschutz/spezifische Rechtsvorschriften für den Stoff oder das Gemisch**
- **TSCA (Toxic Substances Control Act):** All components are on the TSCA inventory

#### · **Hazardous Air Pollutants**

67-56-1 Methanol

#### · **Proposition 65**

#### · **Chemicals known to cause cancer:**

None of the ingredients is listed.

#### · **Chemicals known to cause reproductive toxicity for females:**

67-56-1 Methanol

#### · **Chemicals known to cause reproductive toxicity for males:**

Keiner der Inhaltsstoffe ist enthalten.

#### · **Chemicals known to cause developmental toxicity:**

Keiner der Inhaltsstoffe ist enthalten.

#### · **GHS-Kennzeichnungselemente** entfällt

#### · **Gefahrenpiktogramme** entfällt

(Fortsetzung auf Seite 8)



# Sicherheitsdatenblatt

## gemäß 1907/2006/EG, Artikel 31

Druckdatum: 16.08.2022

Versionsnummer 21

überarbeitet am: 16.08.2022

**Handelsname: EasyFill**

(Fortsetzung von Seite 7)

- **Signalwort** entfällt
- **Gefahrenhinweise** entfällt
- **Stoffsicherheitsbeurteilung:** Eine Stoffsicherheitsbeurteilung wurde nicht durchgeführt.

### 16 Sonstige Angaben

Die Angaben stützen sich auf den heutigen Stand unserer Kenntnisse, sie stellen jedoch keine Zusicherung von Produkteigenschaften dar und begründen kein vertragliches Rechtsverhältnis.

Geänderte Kapitel sind mit einem Stern (\*) gekennzeichnet

#### · **Relevante Sätze**

- H220 Extrem entzündbares Gas.
- H227 Brennbare Flüssigkeit.
- H280 Enthält Gas unter Druck; kann bei Erwärmung explodieren.
- H301 Giftig bei Verschlucken.
- H302 Gesundheitsschädlich bei Verschlucken.
- H310 Lebensgefahr bei Hautkontakt.
- H314 Verursacht schwere Verätzungen der Haut und schwere Augenschäden.
- H315 Verursacht Hautreizungen.
- H317 Kann allergische Hautreaktionen verursachen.
- H318 Verursacht schwere Augenschäden.
- H319 Verursacht schwere Augenreizung.
- H330 Lebensgefahr bei Einatmen.
- H351 Kann vermutlich Krebs erzeugen.

· **Datenblatt ausstellender Bereich:** Produktmanagement

· **Ansprechpartner:**

· **Date of preparation / last revision** 16.08.2022 / 20

#### · **Abkürzungen und Akronyme:**

- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- OSHA: Occupational Safety & Health
- TLV: Threshold Limit Value
- PEL: Permissible Exposure Limit
- REL: Recommended Exposure Limit
- BEI: Biological Exposure Limit
- Entz. Gas 1: Entzündbare Gase – Kategorie 1
- Pressgas: Gase unter Druck – verdichtetes Gas
- Entz. Fl. 4: Entzündbare Flüssigkeiten – Kategorie 4
- Akut Tox. 3: Akute Toxizität – Kategorie 3
- Akut Tox. 4: Akute Toxizität – Kategorie 4
- Akut Tox. 2: Akute Toxizität – Kategorie 2
- Hautätz. 1C: Hautreizende/-ätzende Wirkung – Kategorie 1C
- Hautreiz. 2: Hautreizende/-ätzende Wirkung – Kategorie 2
- Augenschäd. 1: Schwere Augenschädigung/Augenreizung – Kategorie 1
- Eye Irritation 2A: Schwere Augenschädigung/Augenreizung – Kategorie 2A
- Sens. Haut 1: Sensibilisierung der Haut – Kategorie 1
- Sens. Haut 1A: Sensibilisierung der Haut – Kategorie 1A
- Karz. 2: Karzinogenität – Kategorie 2

· **\* Daten gegenüber der Vorversion geändert**