

# LOBA®



# WS EasyFinish

## Description:

LOBA® WS EasyFinish is a high quality one-component waterborne polyurethane finish for use on high traffic residential and light traffic commercial wood and cork floors.

LOBA® WS EasyFinish is an international favorite with a time tested formula. WS EasyFinish levels beautifully and it's proven durability out performs many two-component finishes.

## Features:

- Waterborne Polyurethane formula with excellent wear resistance
- No pot life, no waste, no crosslinker necessary
- Excellent build through high solid content
- No bubbling, beautiful leveling and flow
- Easy to use, can be applied by T-Bar applicator, brush, lambswool or roller
- Available in gloss, semi-gloss and satin
- VOC compliant
- Fast Drying
- No lap marks and streaks
- Proven durability on billions of square feet in over 50 countries
- Water clean-up
- Non-yellowing

## Recommended Use:

### High Traffic Residential:

Kitchens, living rooms, active homes with pets and children.

### Commercial:

Offices, boutiques and specialty shops

# LOBA<sup>®</sup> EasyFinish Technical Data



**Gloss Level:** Satin ( 20°), semi-gloss (40°), gloss (80°)  
**Package Size:** 1 US gallon  
**VOC Content** < 250 grams per liter  
LOBA<sup>®</sup> WS EasyFinish qualifies for LEED credit  
**Range of Use:** Wood and cork floors with normal to heavy wear.  
**Before Use:** Read all instructions and MSDS. Do not thin the product. Keep from freezing. Floor must to be free from wax, oil, dust or dirt. **Shake well before use!**

**Finishing process:** Prepare surface according to NOFMA-accepted method.  
**Wood floors:**  
Apply **WS EasyPrime** and allow to dry thoroughly.  
Apply **LOBA<sup>®</sup> WS EasyFinish** and allow to dry thoroughly.  
Screen with 150 grit screen or maroon pad  
Apply **LOBA<sup>®</sup> WS EasyFinish** (apply an additional coat for high traffic areas)  
**Cork floors:**  
Apply **LOBA<sup>®</sup> WS EasyFinish** and allow to dry thoroughly. Drying over night reduces risk of granule swelling  
Apply **LOBA<sup>®</sup> WS EasyFinish** and allow to dry thoroughly.  
Screen with 150 grit screen or maroon pad  
Apply **LOBA<sup>®</sup> WS EasyFinish**

**Application Tools:** T-Bar Applicator, Lambswool, Brush or Roller  
**Coverage:** 500 - 600 square feet per gallon  
**Dry time:** 2 – 3 hours, light wear after 24 hours, reaches final hardness after approx. 5 days  
**Intercoat Abrasion:** Can be recoated without intercoat abrasion within 24 hours.  
**Thinner:** The finish is ready-to-use. Do not thin. If necessary the Drying can be delayed by adding a maximum of 5% **LOBA<sup>®</sup> WS Argo**.

**Storage and Transportation** Store and transport between 41°F to 77°F. Shelf life 12 months in opened container.  
**Recoating of Prefinished Wood Floors** Prefinished wood floors can be recoated without sanding if **LOBA<sup>®</sup> WS 2K Contact** primer is used as adhesion promoter before coating. We recommend to topcoat **LOBA<sup>®</sup> WS 2K Contact** with **LOBA<sup>®</sup> WS 2K Supra** to achieve a comparable durability to modern UV-curing finishes.

**General Information** The general Information on the use of LOBA products is part of this information and should be read before applying Loba products. When this product is used in combination with other LOBA products also the technical information of these products has to be followed. While Information and data contained herein is presented in good faith and is believed to be reliable, they do not constitute any part of our terms and conditions of sale. Applicator or end user is required to read and understand all information contained on package labels. Additional technical information is also available by visiting our website. If any results achieved during application are less than satisfactory, stop application and contact our technical department.

Loba-Wakol, LLC  
1604 N. Main St.  
Kannapolis, NC 28081  
Phone (800) 230-6456  
Fax (704) 932-3041  
www.loba-wakol.com

revised: June 2009

