

LOBA®



WS EasyPrime



Description:

LOBA® WS EasyPrime is a waterborne sealer for wood floors

Features:

- Reduces side bonding
- Suitable for most common wood species
- Can be finished with all Loba waterborne finishes
- No bubbling, beautiful leveling and flow
- Easy to use, can be applied by T-Bar applicator, brush, lambswool or roller
- Non-yellowing protects the natural color of the wood
- VOC compliant
- Fast Drying
- No lap marks and streaks

Recommended Use:

Under all Loba Waterborne Finishes

Suitable for all common wood species except:

Arrurra Velmelho, Ipe/Lapacho, Iroko/Kambala, Mohuhu, Piguia Marfin, Pear, Purpleheart (see suitability list).

LOBA® EasyPrime Technical Data



Package Size:	1 US gallon
VOC Content	< 190 grams per liter
Range of Use:	Waterborne Sealer for wood floors
Before Use:	Read all instructions and MSDS. Do not thin the product. Keep from freezing. Floor must to be free from wax, oil, dust or dirt. Shake well before use!
Finishing process:	Prepare surface according to NOFMA-accepted method. Apply LOBA® WS EasyPrime . Allow 60 minute minimum drytime When thoroughly dry apply a LOBA waterborne finish LOBA® Viva for residential floors LOBA® WS EasyFinish for high traffic residential and light commercial LOBA® WS 2K Supra for commercial high traffic
Application Tools:	T-Bar Applicator, Lambswool, Brush or Roller
Coverage:	400 - 500 square feet per gallon
Dry time:	1 – 2 hours
Intercoat Abrasion:	LOBA generally does not recommend to sand waterborne sealers because of the danger to sand through.
Thinner:	The finish is ready-to-use. Do Not Thin!
Storage and Transportation	Store and transport between 41°F to 77°F. Shelf life 12 months in unopened container
General Information	The general Information on the use of LOBA products is part of this information and should be read before applying Loba products. When this product is used in combination with other LOBA products also the technical information of these products has to be followed. While Information and data contained herein is presented in good faith and is believed to be reliable, they do not constitute any part of our terms and conditions of sale. Applicator or end user is required to read and understand all information contained on package labels. Additional technical information is also available by visiting our website. If any results achieved during application are less than satisfactory, stop application and contact our technical department.

Loba-Wakol, LLC
1604 N. Main St.
Kannapolis, NC 28081
Phone (800) 230-6456
Fax (704) 932-3041
www.loba-wakol.com

revised: June 2009

