Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

	: Identification of the substance/mixture and of the	company/undertaking
· 1.1 Product ide	ntifier	
Product name S	Stain Jacobean	
1.2 Relevant id No further relev	: 11525-800200-000 entified uses of the substance or mixture and uses advised ag vant information available. the substance / the mixture	ainst
Manufacturer/A LOBA GmbH & Leonberger Stra D-71254 Ditzin United Kingdon	с Со. КG 1βе 56 - 62 gen	Tel.: +49 (0)7156/357
Phi House Southampton Southampton, S United Kingdom Phone +442380	n n	
1.4 Emergency	urtment: service@loba.de telephone number: NTACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463	
	: Hazards identification on of the substance or mixture according to Regulation (EC) No 1272/2008	
Classification a	on of the substance or mixture according to Regulation (EC) No 1272/2008	
Classification a flame Flam. Liq. 2 H. 2.2 Label eleme Labelling accord	on of the substance or mixture according to Regulation (EC) No 1272/2008 225 Highly flammable liquid and vapour. 22ts Paing to Regulation (EC) No 1272/2008 Classified and labelled according to the GB CLP regulation.	
Classification a flame Flam. Liq. 2 H. 2.2 Label eleme Labelling accor The product is c	on of the substance or mixture according to Regulation (EC) No 1272/2008 225 Highly flammable liquid and vapour. 22ts Paing to Regulation (EC) No 1272/2008 Classified and labelled according to the GB CLP regulation.	
Classification a Flam. Liq. 2 Hi 2.2 Label eleme Labelling accord The product is condition Hazard pictogra GHS02 Signal word Data Hazard statement H225 Highly flat	on of the substance or mixture according to Regulation (EC) No 1272/2008 225 Highly flammable liquid and vapour. 225 Highly flammable liquid and vapour. 225 Highly flammable liquid and vapour. 225 Highly flammable liquid according to the GB CLP regulation. 2008 2009 2009 2009 2009 2009 2009 2009	
Classification a flame Flam. Liq. 2 H. 2.2 Label eleme Labelling accor The product is of Hazard pictogra GHS02 Signal word Da Hazard statement H225 Highly fla Precautionary s P101 P102	on of the substance or mixture according to Regulation (EC) No 1272/2008 225 Highly flammable liquid and vapour. 225 Highly flammable liquid and vapour. 225 Highly flammable liquid and vapour. 225 Highly flammable liquid (EC) No 1272/2008 238 classified and labelled according to the GB CLP regulation. 248 classified and labelled according to the GB CLP regulation. 249 classified and labelled according to the GB CLP regulation. 250 classified and labelled according to the GB CLP regulation. 250 classified and vapour. 251 classified and vapour. 251 classified advice is needed, have product container or lab 252 classified advice is needed, have product container or lab 253 classified advice is needed, have product container or lab 254 classified advice is needed.	bel at hand.
Classification a flame Flam. Liq. 2 Hi 2.2 Label eleme Labelling accord The product is a Hazard pictogra GHS02 Signal word Da Hazard statement H225 Highly flat Precautionary s P101	on of the substance or mixture according to Regulation (EC) No 1272/2008 225 Highly flammable liquid and vapour. 225 Highly flammable liquid and vapour. 225 Highly flammable liquid and vapour. 225 Highly flammable liquid according to the GB CLP regulation. 225 Highly flammable liquid and vapour. 225 Highly flammable liquid and vapour. 236 Statements 24 If medical advice is needed, have product container or lab	and other ignition sources. N

*

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024 Vers

Version number 5 (replaces version 4)

Revision: 04.03.2024

Product name Stain Jacobean

P501	present and eas	Rinse cautiously with water for several minutes. Remove conta sy to do. Continue rinsing. ntents/container in accordance with local/regional/national/in	-
2.3 Other ha Results of P PBT: Not ap vPvB: Not a	uzards BT and vPvB assessm oplicable.	ent	
3.2 Mixtures	5	nformation on ingredients nces listed below with harmless additions.	
Dangerous d	components:		
CAS: 64-17- EINECS: 20	0-578-6 er: 603-002-00-5	ethanol ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	25-50%
	211945/010-45-XXXX		05 500/
Reg.nr.: 01 CAS: 34590 EINECS: 25	-94-8	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	25-50%

• Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation Supply fresh air; consult doctor in case of symptoms.

· After skin contact

In general, the product is not irritating to the skin. Wash off the product with plenty of soap and water after skin contact.

- · After eye contact Rinse opened eye for several minutes under running water.
- *After swallowing* In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed Symptom Treat omatically.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents
- Water.
- Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

GB

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024

Version number 5 (replaces version 4)

Revision: 04.03.2024

Product name Stain Jacobean

(Contd. of page 2)
 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies. Prevent material from reaching sewage system, holes and cellars. Inform respective authorities in case product reaches water or sewage system. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents 6.4 Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.
SECTION 7: Handling and storage
 7.1 Precautions for safe handling Keep containers tightly sealed. Store in cool, dry conditions in well sealed containers. Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
 7.2 Conditions for safe storage, including any incompatibilities Storage Requirements to be met by storerooms and containers: Store in cool location. Information about storage in one common storage facility: Not required. Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed containers. Storage class 3 7.3 Specific end use(s) No further relevant information available.
SECTION 8: Exposure controls/personal protection
· 8.1 Control parameters
• Components with critical values that require monitoring at the workplace:
64-17-5 ethanol
WEL Long-term value: 1920 mg/m ³ , 1000 ppm
34590-94-8 Dipropylene glycol monomethyl ether
WEL Long-term value: 308 mg/m ³ , 50 ppm Sk

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV

· Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

• Appropriate engineering controls No further data; see section 7.

(Contd. on page 4)

GB

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024

Version number 5 (replaces version 4)

Revision: 04.03.2024

(Contd. of page 3)

Product name Stain Jacobean

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures Wash hands during breaks and at the end of the work.
- · Breathing equipment: Not required.
- · Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves
- Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Recommended thickness of the material: ≥ 0.4 mm
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level ≤ 6

• Eye/face protection Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical p	roperties
· General Information	
· Physical state	Fluid
Colour:	According to product specification
- Smell:	Recognisable
· Odour threshold:	Not determined.
• Melting point/freezing point:	Not determined
· Boiling point or initial boiling point and boiling	
range	Not determined
· Flammability	Highly flammable.
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	17 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic:	Not determined.
Solubility	
· Water:	Not miscible or difficult to mix
· Partition coefficient n-octanol/water (log value)	Not determined.
Steam pressure:	Not determined.
Density and/or relative density	
· Density at 20 °C	$0.89 \ g/cm^3$
· Relative density	Not determined.
· Vapour density	Not determined.
· Particle characteristics	not applicable, as liquid
• 9.2 Other information	
· Appearance:	
· Form:	Fluid
	(Contd. on page 5)

GE

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024

Version number 5 (replaces version 4)

Revision: 04.03.2024

Product name Stain Jacobean

	(Contd. of page 4
Important information on protection of heal	lth and
environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard	classes
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamm	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values th	at are relevan	t for cl	assification:
-----------	-----------	----------------	----------	---------------

64-17-5 et	hanal	
04-1/-5 et	nanoi	
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)
34590-94-	8 Dipropyl	ene glycol monomethyl ether
Oral	LD50	5,135 mg/kg (rat)
Dermal	LD50	9,500 mg/kg (rat)
78-93-3 bi	itanone	
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	12,000 mg/l (rat)
		(Contd. on page

GB

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024

Version number 5 (replaces version 4)

Revision: 04.03.2024

(Contd. of page 5)

Product name Stain Jacobean

- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity* Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met. • Aspiration hazard Based on available data, the classification criteria are not met.
- Aspiration nazara Basea on available data, the classification • 11.2 Information on other hazards
- Endocrine disrupting properties

78-93-3 butanone

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

· Uncleaned packagings:

• *Recommendation: Disposal must be made according to official regulations.*

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
·ADR	1263 PAINT (vapour pressure at 50°C not more tha
	110 kPa)
· IMDG, IATA	PAINT

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024

Version number 5 (replaces version 4)

Revision: 04.03.2024

Product name Stain Jacobean

	(Contd. of page
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
· Class	3 Flammable liquids.
· Label	3
· 14.4 Packing group · ADR, IMDG, IATA	П
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
· Kemler Number:	33
EMS Number:	F-E, <u>S-E</u> B
Stowage Category	2
14.7 Maritime transport in bulk according	
instruments	Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml
Transport category Tunnel restriction code	Maximum net quantity per outer packaging: 500 ml 2 D/E
IMDG	
Limited quantities (LQ)	5L
\cdot Excepted quantities ($\widetilde{E}Q$)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NC MORE THAN 110 KPA), 3, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture • Poisons Act
- · Regulated explosives precursors

None of the ingredients is listed.

- · Regulated poisons
- None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

(Contd. on page 8)

GB

according to Regulation (EC) No 1907/2006, Article 31

Printing date 04.03.2024

Version number 5 (replaces version 4)

Revision: 04.03.2024

(Contd. of page 7)

Product name Stain Jacobean

- Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· National regulations

- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing data specification sheet: Product safety

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 • * Data compared to the previous version altered.