	dentification of the substance/mixture and of the con	nnany/undartabing
		ipuny/undertuking
1.1 Product identi	•	
· Product name <u>Sta</u>	in Sedona Red	
No further relevan	1525-800147-000 tified uses of the substance or mixture and uses advised against at information available. e substance / the mixture	
• 1.3 Details of the • Manufacturer/Su LOBA GmbH & C Leonberger Straße D-71254 Ditzinge	o. KG e 56 - 62	Tel.: +49 (0)7156/357-
United Kingdom: Phi House Southampton Scie Southampton, SOJ United Kingdom	nce Park	1et + + y (0)/130/35/-
Phone +44238070	66722	
· Informing depart · 1.4 Emergency te	ment: service@loba.de Ienhone number:	
	ACT (24-Hour-Number):GBK GmbH +49 (0)6132-84463	
2.1 Classification	Hazards identification of the substance or mixture ording to Regulation (EC) No 1272/2008	
2.1 Classification Classification acc flame Flam. Liq. 2 H22 2.2 Label element Labelling accordi The product is cla	of the substance or mixture Fording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. Ts ng to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation.	
2.1 Classification Classification acc flame Flam. Liq. 2 H22 2.2 Label element Labelling accordi The product is cla Hazard pictogram	of the substance or mixture Fording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. Ts ng to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation.	
2.1 Classification Classification acc flame Flam. Liq. 2 H22 2.2 Label element Labelling accordi The product is cla	of the substance or mixture Fording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. Ts ng to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation.	
2.1 Classification Classification acc flame Flam. Liq. 2 H22 2.2 Label element Labelling accordi The product is cla Hazard pictogram GHS02 Signal word Dang Hazard statement H225 Highly flam	of the substance or mixture cording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. ts ing to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation. ts ger ss mable liquid and vapour.	
 2.1 Classification acc Classification acc Classification acc flame Flam. Liq. 2 H22 2.2 Label element Labelling accordi The product is cla Hazard pictogram GHS02 Signal word Dang Hazard statement H225 Highly flam Precautionary sta 	of the substance or mixture cording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. ts ing to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation. ts ger s mable liquid and vapour. tements	hand
2.1 Classification Classification acc flame Flam. Liq. 2 H22 2.2 Label element Labelling accordi The product is cla Hazard pictogram GHS02 Signal word Dang Hazard statement H225 Highly flam	of the substance or mixture cording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. ts ing to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation. ts ger ss mable liquid and vapour.	hand.
 2.1 Classification acc Classification acc flame Flam. Liq. 2 H22 2.2 Label element Labelling accordi The product is cla Hazard pictogram GHS02 Signal word Dang Hazard statement H225 Highly flam Precautionary sta P101 P102 P103 	of the substance or mixture cording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. 5 7 8 7 9 7 9 7 9 7 9 8 7 9 8 7 9 7 9 7 9	
 2.1 Classification acc Classification acc Classification acc flame Flam. Liq. 2 H22 2.2 Label element Labelling accordi The product is cla Hazard pictogram GHS02 Signal word Dang Hazard statement H225 Highly flam Precautionary sta P101 P102 	of the substance or mixture cording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. 5 ng to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation. 15 ger 5 mable liquid and vapour. tements If medical advice is needed, have product container or label at Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat, hot surfaces, sparks, open flames and	
 2.1 Classification acc Classification acc flame Flam. Liq. 2 H22 2.2 Label element Labelling accordi The product is cla Hazard pictogram GHS02 Signal word Dang Hazard statement H225 Highly flam Precautionary sta P101 P102 P103 	of the substance or mixture fording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. 5 ing to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation. 15 s ger 5 mable liquid and vapour. tements If medical advice is needed, have product container or label at Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat, hot surfaces, sparks, open flames and smoking.	other ignition sources. N
 2.1 Classification acc Classification acc flame Flam. Liq. 2 H22. 2.2 Label element Labelling accordi The product is cla Hazard pictogram GHS02 Signal word Dang Hazard statement H225 Highly flam Precautionary sta P101 P102 P103 P210 P241 P280 	of the substance or mixture ording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. 5s ing to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation. 1s s ger 5s mable liquid and vapour. tements If medical advice is needed, have product container or label at Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat, hot surfaces, sparks, open flames and smoking. Use explosion-proof [electrical/ventilating/lighting] equipment Wear protective gloves / eye protection.	other ignition sources. N
 2.1 Classification acc Classification acc flame Flam. Liq. 2 H22. 2.2 Label element Labelling accordi The product is cla Hazard pictogram GHS02 Signal word Dang Hazard statement H225 Highly flam Precautionary sta P101 P102 P103 P210 P241 P280 	of the substance or mixture fording to Regulation (EC) No 1272/2008 5 Highly flammable liquid and vapour. 5 ing to Regulation (EC) No 1272/2008 ssified and labelled according to the GB CLP regulation. 15 s ger 5 mable liquid and vapour. tements If medical advice is needed, have product container or label at Keep out of reach of children. Read carefully and follow all instructions. Keep away from heat, hot surfaces, sparks, open flames and smoking. Use explosion-proof [electrical/ventilating/lighting] equipment	other ignition sources. N

*

Printing date 12.09.2023

Version number 2 (replaces version 1)

Revision: 12.09.2023

Product name Stain Sedona Red

(Contd. of page 1) P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. • 2.3 Other hazards • Results of PBT and vPvB assessment • PBT: Not applicable. • vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· Description: Mixture of the substances listed below with harmless additions.

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-xxxx	ethanol ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	≥25-<50%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-211-945-0011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	25-50%
CAS: 1309-37-1	<i>Pigment Red 101</i> substance with a Community workplace exposure limit	2.5-5%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-xxxx	butanone	<0.5%

• Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation Supply fresh air; consult doctor in case of symptoms.

• After skin contact The product is not skin irritating.

• After eye contact Rinse opened eye for several minutes under running water.

• After swallowing In case of persistent symptoms consult doctor.

- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- \cdot For safety reasons unsuitable extinguishing agents

Water.

- Water with a full water jet.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 3)

^{· 3.2} Mixtures

Printing date 12.09.2023

*

*

Version number 2 (replaces version 1)

Revision: 12.09.2023

Product name Stain Sedona Red

(Contd. of page 2)

SECTION 6: Accidental release measures
 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away. 6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies. Prevent material from reaching sewage system, holes and cellars. Inform respective authorities in case product reaches water or sewage system. 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents 6.4 Reference to other sections See Section 7 for information on safe handling See Section 13 for information on disposal.
SECTION 7: Handling and storage
7.1 Precautions for safe handling Keep containers tightly sealed. Store in cool, dry conditions in well sealed containers. Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
 7.2 Conditions for safe storage, including any incompatibilities Storage Requirements to be met by storerooms and containers: Store in cool location. Information about storage in one common storage facility: Not required. Further information about storage conditions: Keep container tightly sealed. Store in cool, dry conditions in well sealed containers. Storage class 3 7.3 Specific end use(s) No further relevant information available.
SECTION 8: Exposure controls/personal protection
SECTION 6. Exposure controls/personal protection
8.1 Control parameters
Company and a with a with a first on the standing on a with since at the superhale and

• Components with critical values that require monitoring at the workplace:
64-17-5 ethanol
WEL Long-term value: 1920 mg/m ³ , 1000 ppm
34590-94-8 Dipropylene glycol monomethyl ether
WEL Long-term value: 308 mg/m ³ , 50 ppm Sk
1309-37-1 Pigment Red 101
WEL Short-term value: 10* mg/m ³ Long-term value: 5* 10** 4*** mg/m ³ *fume (as Fe),**total respirable,***respirable
78-93-3 butanone
WEL Short-term value: 899 mg/m ³ , 300 ppm Long-term value: 600 mg/m ³ , 200 ppm Sk, BMGV
(Contd. on page 4)

GB GB

Printing date 12.09.2023

Version number 2 (replaces version 1)

Revision: 12.09.2023

Product name Stain Sedona Red

gredients with biological limit values: L-93-3 butanone MGV 70 µmol/L Medium: wrine Sampling time: post shift Parameter: butan-2-one Iditional information: The lists that were valid during the 2 Exposure controls porporiate engineering controls No further data; see sectid dividual protection measures, such as personal protective eneral protective and hygienic measures Wash hands duri reathing equipment: Not required. and protection votective gloves. teg glove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation aterial of gloves trile rubber, NBR teg selection of the suitable gloves does not only depend on ud varies from manufacturer to manufacturer. As the pro sistance of the glove material tee exact break trough time has to be found out by the marker served. or the mixture of chemicals mentioned below the pener termeation according to EN 374 Part 3: Level 6). uhe for the permeation: Level ≤ 6 preface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties </th <th>7. Equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t</th>	7. Equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t
Medium: urine Sampling time: post shift Parameter: butan-2-one Iditional information: The lists that were valid during the 2 Exposure controls popopriate engineering controls No further data; see section dividual protection measures, such as personal protective eneral protective and hygienic measures Wash hands during reathing equipment: Not required. and protection rotective gloves. net glove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation attrile rubber, NBR the selection of the suitable gloves does not only depend on ad varies from manufacturer to manufacturer. As the prosistance of the glove material can not be calculated in adverse plication. commended thickness of the material: $\geq 0.4 \text{mm}$ eneration time of glove material we exact break trough time has to be found out by the material served. or the mixture of chemicals mentioned below the perference refface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties eneral Information hysical state Fluid holour: Accordi. nell:	7. Equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t
Medium: urine Sampling time: post shift Parameter: butan-2-one Iditional information: The lists that were valid during the 2 Exposure controls popopriate engineering controls No further data; see section dividual protection measures, such as personal protective eneral protective and hygienic measures Wash hands during reathing equipment: Not required. and protection rotective gloves. net glove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation attrile rubber, NBR the selection of the suitable gloves does not only depend on ad varies from manufacturer to manufacturer. As the prosistance of the glove material can not be calculated in adverse plication. commended thickness of the material: $\geq 0.4 \text{mm}$ eneration time of glove material we exact break trough time has to be found out by the material served. or the mixture of chemicals mentioned below the perference refface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties eneral Information hysical state Fluid holour: Accordi. nell:	7. Equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t
Sampling time: post shift Parameter: butan-2-one Aditional information: The lists that were valid during the 2 Exposure controls poppopriate engineering controls No further data; see section dividual protection measures, such as personal protective eneral protective and hygienic measures Wash hands duri- reathing equipment: Not required. and protection oractive gloves. te glove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation aterial of gloves trile rubber, NBR te selection of the suitable gloves does not only depend on of varies from manufacturer to manufacturer. As the pro- sistance of the glove material can not be calculated in adv uplication. commended thickness of the material: ≥ 0.4 mm enteration time of glove material the exact break trough time has to be found out by the manufacturer. served. or the mixture of chemicals mentioned below the per- vermeation according to EN 374 Part 3: Level 6). tue for the permeation: Level ≤ 6 perface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties eneral Information mysical state plour: Accordit measure the permeasion: Level ≤ 6 polour: Accordit measure the permeasion on basic physical and chemical properties eneral Information mysical state full Not detection polour: Not detection polour: <	7. Equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t
Parameter: butan-2-one Iditional information: The lists that were valid during the 2 Exposure controls popropriate engineering controls No further data; see section dividual protection measures, such as personal protective eneral protective and hygienic measures Wash hands during the reathing equipment: Not required. and protection rotective gloves. the glove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation aterial of gloves trile rubber, NBR te selection of the suitable gloves does not only depend on the varies from manufacturer to manufacturer. As the prosisistance of the glove material can not be calculated in adviplication. ecommended thickness of the material: ≥ 0.4 mm the exact break trough time has to be found out by the material served. or the mixture of chemicals mentioned below the performation according to EN 374 Part 3: Level 6). tue for the permeation: Level ≤ 6 tereface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties eneral Information mysical state Fluid obour: Accordit mell: Recognit down threshold: Not detter <t< td=""><td>7. Equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t</td></t<>	7. Equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t
2 Exposure controls 2 Exposure controls oppropriate engineering controls No further data; see sected dividual protection measures, such as personal protective eneral protective and hygienic measures Wash hands during reathing equipment: Not required. and protection rotective gloves. teglove material has to be impermeable and resistant to the legradation aterial of gloves trile rubber, NBR te selection of the suitable gloves does not only depend on of varies from manufacturer to manufacturer. As the prosistance of the glove material can not be calculated in adv pplication. ccommended thickness of the material: ≥ 0.4 mm exerved. or the mixture of chemicals mentioned below the pender or the permeation: Level ≤ 6 tegface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties polour: Accordit negling point or initial boiling point and boiling ing Mot dete protection Not dete etaing point or initial boiling point and boiling Mot dete protection Not dete part as the perine	7. Equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t
2 Exposure controls 2 Exposure controls oppropriate engineering controls No further data; see sected dividual protection measures, such as personal protective eneral protective and hygienic measures Wash hands during reathing equipment: Not required. and protection rotective gloves. teglove material has to be impermeable and resistant to the legradation aterial of gloves trile rubber, NBR te selection of the suitable gloves does not only depend on of varies from manufacturer to manufacturer. As the prosistance of the glove material can not be calculated in adv pplication. ccommended thickness of the material: ≥ 0.4 mm exerved. or the mixture of chemicals mentioned below the pender or the permeation: Level ≤ 6 tegface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties polour: Accordit negling point or initial boiling point and boiling ing Mot dete protection Not dete etaing point or initial boiling point and boiling Mot dete protection Not dete part as the perine	7. Equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t
proprivate engineering controls No further data; see sectiondividual protection measures, such as personal protectiveeneral protective and hygienic measures Wash hands duri-erathing equipment: Not required.and protectionrotective gloves.teg glove material has to be impermeable and resistant to theelection of the glove material on consideration of thegradationaterial of glovestrile rubber, NBRte selection of the suitable gloves does not only depend ond'varies from manufacturer to manufacturer. As the prosistance of the glove material can not be calculated in advprotection.ecommended thickness of the material: ≥ 0.4 mmentertation time of glove materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the material served.the full of the permeation: Level ≤ 6 the face protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties the meating point or initial boiling point and boilingnell:Recognitour:Not detepoing point or initial boiling point and boilingnge<	equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t
dividual protection measures, such as personal protective eneral protective and hygienic measures Wash hands duri- reathing equipment: Not required.and protection otective gloves.be glove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation aterial of gloves trile rubber, NBR be selection of the suitable gloves does not only depend on of varies from manufacturer to manufacturer. As the pro- sistance of the glove material can not be calculated in adv uplication. ecommended thickness of the material: ≥ 0.4 mm emetration time of glove material be exact break trough time has to be found out by the materiserved. or the mixture of chemicals mentioned below the performation according to EN 374 Part 3: Level 6). thue for the permeation: Level ≤ 6 ECTION 9: Physical and chemical properties emeral Information mysical stateFluid olour: Accordi. mell: dour threshold: elting point/freezing point: out the matherial boling point or initial boiling point and boiling inge mammabilityNot dete ammabilityMot dete Highly former: Not dete fash point:Not dete fash point:Not dete Highly former: Not dete Not dete Not dete Not dete fash point:	equipment g breaks and at the end of the work. product/ the substance/ the preparation. benetration times, rates of diffusion and t
eneral protective and hygienic measures Wash hands duri. reathing equipment: Not required. and protection rotective gloves. reglove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation aterial of gloves trile rubber, NBR reselection of the suitable gloves does not only depend on the varies from manufacturer to manufacturer. As the prosistance of the glove material can not be calculated in adverse splication. ecommended thickness of the material: $\geq 0.4 \text{ mm}$ enertation time of glove material execommended thickness of the material: $\geq 0.4 \text{ mm}$ enertation time of glove material execommended thickness of the material: $\geq 0.4 \text{ mm}$ enertation time of glove material execommended thickness of the material: $\geq 0.4 \text{ mm}$ entertation time of glove material execommended thickness of the material: $\geq 0.4 \text{ mm}$ entertation time of glove material execommended thickness of the material: $\geq 0.4 \text{ mm}$ entertation time of glove material execommended thickness of the material: $\geq 0.4 \text{ mm}$ entertation time of glove material execommended thickness of the material: $\geq 0.4 \text{ mm}$ entertation according to EN 374 Part 3: Level 6).	g breaks and at the end of the work. product/ the substance/ the preparation. penetration times, rates of diffusion and t
reathing equipment: Not required. and protection rotective gloves. he glove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation aterial of gloves trile rubber, NBR he selection of the suitable gloves does not only depend on the varies from manufacturer to manufacturer. As the prosisistance of the glove material can not be calculated in adverge of the glove material is $\geq 0.4 \text{ mm}$ remetration time of glove material he exact break trough time has to be found out by the material served. for the mixture of chemicals mentioned below the permetration according to EN 374 Part 3: Level 6). alue for the permeation: Level ≤ 6 the formation on basic physical and chemical properties eneral Information by the seled safety glasses. ECTION 9: Physical and chemical properties for threshold: Not deteen the selection of the selection formation by the selection of the permeation according to EN 374 Part 3: Level 6). and formation according to EN 374 Part 3: Level 6). angle in the permeation: Level ≤ 6 terface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties eneral Information hysical state Fluid </td <td>product/ the substance/ the preparation. benetration times, rates of diffusion and t</td>	product/ the substance/ the preparation. benetration times, rates of diffusion and t
and protection rotective gloves. he glove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation aterial of gloves trile rubber, NBR he selection of the suitable gloves does not only depend on od varies from manufacturer to manufacturer. As the pro- sistance of the glove material can not be calculated in adv oplication. ecommended thickness of the material: ≥ 0.4 mm emetration time of glove material he exact break trough time has to be found out by the material he exact break trough time has to be found to below the perfection he to be perfection Tightly seal	penetration times, rates of diffusion and t
protective gloves. are glove material has to be impermeable and resistant to the election of the glove material on consideration of the gradation aterial of gloves trile rubber, NBR be selection of the suitable gloves does not only depend on on d varies from manufacturer to manufacturer. As the prosistance of the glove material can not be calculated in adverglication. be selection of the suitable gloves does not only depend on on the varies from manufacturer to manufacturer. As the prosistance of the glove material can not be calculated in adverglication. be commended thickness of the material: ≥ 0.4 mm commation according to EN 374 Part 3: Level	penetration times, rates of diffusion and t
The glove material has to be impermeable and resistant to the decision of the glove material on consideration of the gradationaterial of glovesaterial of glovestrile rubber, NBRthe selection of the suitable gloves does not only depend onto varies from manufacturer to manufacturer. As the prosisitance of the glove material can not be calculated in adverseprovide thickness of the material: ≥ 0.4 mmthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe exact break trough time has to be found out by the materialthe mixture of chemicals mentioned below the permeation according to EN 374 Part 3: Level 6).thue for the permeation: Level ≤ 6 the face protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties the materialthe metrial point or initial boiling point and boilingngefulling point or initial boiling point and boilingngematerial point:the full pointthe full point <tr< td=""><td>penetration times, rates of diffusion and t</td></tr<>	penetration times, rates of diffusion and t
election of the glove material on consideration of the gradation aterial of gloves trile rubber, NBR the selection of the suitable gloves does not only depend on the varies from manufacturer to manufacturer. As the prosisistance of the glove material can not be calculated in adverse science of the glove material can not be calculated in adverse science. execommended thickness of the material: ≥ 0.4 mm entertation time of glove material the exact break trough time has to be found out by the materials the exact break trough time has to be found out by the material according to EN 374 Part 3: Level 6). the for the permeation: Level ≤ 6 the for the permeation: Level ≤ 6 the formation on basic physical and chemical properties eneral Information mysical state Fluid polour: Accordit nell: Recogni down threshold: Not dete poling point or initial boiling point and boiling mighty flighty forwer: policy Not dete policy Not dete fingeper: Not dete	penetration times, rates of diffusion and t
gradationaterial of glovestrile rubber, NBRthe selection of the suitable gloves does not only depend onad varies from manufacturer to manufacturer. As the pro-sistance of the glove material can not be calculated in advipplication.ecommended thickness of the material:exect break trough time has to be found out by the manufacture of chemicals mentioned below the performation according to EN 374 Part 3: Level 6).the for the permeation: Level ≤ 6 the exact break trough time has to safety glasses.ECTION 9: Physical and chemical propertiesInformation on basic physical and chemical propertiesthe permeation intial boiling point and boilingngeNot deterpoint or initial boiling point and boilingngeNot deterpartsNot deterpermetailityNot deterpartsNot deterpermetailitynot deterpermetailitynot deterpermetailitynot deterpermetailitynot deterpermetailitynot deterpermetailitynot deterpermetailitynot deterpermetailitypermetailitynot deterpermetailitynot deterpermetailitynot deterpermetailitynot deterpermetailitynot deterpermetailitynot deterpermetaility <th< td=""><td></td></th<>	
aterial of gloves trile rubber, NBR te selection of the suitable gloves does not only depend on d varies from manufacturer to manufacturer. As the pro- sistance of the glove material can not be calculated in adv uplication. ecommended thickness of the material: ≥ 0.4 mm emetration time of glove material the exact break trough time has to be found out by the manufacture of chemicals mentioned below the performation according to EN 374 Part 3: Level 6). The mixture of chemicals mentioned below the performation according to EN 374 Part 3: Level 6). The permeation: Level ≤ 6 the permeation Tightly sealed safety glasses.ECTION 9: Physical and chemical properties eneral Information mysical stateFluid Not detection Tightly for the permetion: Not detecting point or initial boiling point and boiling power: Not detections: Not detections: <b< td=""><td></td></b<>	
trile rubber, NBRthe selection of the suitable gloves does not only depend onad varies from manufacturer to manufacturer. As the prosisitance of the glove material can not be calculated in advsistance of the glove material can not be calculated in advpplication.ecommended thickness of the material: $\geq 0.4 \text{ mm}$ emetration time of glove materialthe exact break trough time has to be found out by the manufacture of chemicals mentioned below the performancethe mixture of chemicals mentioned below the performancethe mixture of chemicals mentioned below the performancethe permeation according to EN 374 Part 3: Level 6).thue for the permeation: Level ≤ 6 the for the permeation Tightly sealed safety glasses. ECTION 9: Physical and chemical propertiesInformation on basic physical and chemical properties eneral Informationhysical statepolour:holour:holour:holour:holour threshold:poling point or initial boiling point and boilingngeNot detepoling point or initial boiling point and boilingngeNot detepart in this point:Not detepart in this point:Not detepart in this point:Not detepart in this point:hour threshold:hour threshold:hour threshold:hour threshold:hour threshold:hour threshold:hour threshold:hour threshold:hour threshold: </td <td></td>	
The selection of the suitable gloves does not only depend on ad varies from manufacturer to manufacturer. As the prosistance of the glove material can not be calculated in adversion sistance of the glove material can not be calculated in adversion production. ecommended thickness of the material: ≥ 0.4 mm pretration time of glove material the exact break trough time has to be found out by the manufacture of chemicals mentioned below the performance the mixture of chemicals mentioned below the performation according to EN 374 Part 3: Level 6). the permeation: Level ≤ 6 the performation on basic physical and chemical properties Perface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties Information on basic physical and chemical properties provide the shold: Not dete point threshold: Not dete point or initial boiling point and boiling Not dete pore: Not dete pore: Not dete point: Not dete	, , 1 1 , 1 , 0 , 1 , 1 , 0 ,
ad varies from manufacturer to manufacturer. As the prosisitance of the glove material can not be calculated in advsistance of the glove material can not be calculated in advpplication.ecommended thickness of the material: $\geq 0.4 \text{ mm}$ enetration time of glove materialthe exact break trough time has to be found out by the manufacture of chemicals mentioned below the performent of a cording to EN 374 Part 3: Level 6).the for the permeation: Level ≤ 6 the for the permeation: Level ≤ 6 the for the permeation: Level ≤ 6 the formation on basic physical and chemical propertiesthe formation on basic physical and chemical propertiesthe point freezing point:how threshold:the formabilitythe point or initial boiling point and boilingngeNot detertammabilitytable point:Not detertammabilitytable point:Not detertammabilitytable point:table point:	ie material, but also on further marks of qual
sistance of the glove material can not be calculated in adv pplication. ecommended thickness of the material: $\geq 0.4 \text{ mm}$ enertation time of glove material the exact break trough time has to be found out by the man- preserved. for the mixture of chemicals mentioned below the pen- termeation according to EN 374 Part 3: Level 6). alue for the permeation: Level ≤ 6 the face protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties al Information on basic physical and chemical properties eneral Information thysical state Fluid blour: According the threshold: Not detect beling point or initial boiling point and boiling mge Not detect basic physical and boiling mge Not detect bower: Not detect ash point: 17 °C	
pplication.production.procommended thickness of the material:procentration time of glove materialpreserved.prot the mixture of chemicals mentioned below the performation according to EN 374 Part 3: Level 6).prot the permeation: Level ≤ 6 proface protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties1 Information on basic physical and chemical properties1 Information1 mysical state1 model1 model <	
enertration time of glove materialthe exact break trough time has to be found out by the managementthe exact break trough time has to be found out by the managementthe mixture of chemicals mentioned below the pertinethe permeation: Level ≤ 6 the permeation Tightly sealed safety glasses.ECTION 9: Physical and chemical propertiesInformation on basic physical and chemical propertieseneral InformationMot detetopolour:Accordiahour threshold:Not deteelting point/freezing point:Not detebiling point or initial boiling point and boilingNot detemanabilityHighly fower:Not deteoper:Not deteash point:17 °C	v i
the exact break trough time has to be found out by the manager ved. For the mixture of chemicals mentioned below the peri- fermeation according to EN 374 Part 3: Level 6). The permeation: Level ≤ 6 the face protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties ECTION 9: Physical and chemical properties teneral Information thysical state Fluid blour: Accordian thysical state Fluid blour: Accordiant the properties for the permeasing point: Not deter biling point or initial boiling point and boiling mge Not deter bower: Not deter by per: Not deter ash point: 17 °C	
Inserved.for the mixture of chemicals mentioned below the peri-for the mixture of chemicals mentioned below the peri-for the permeation: Level ≤ 6 for the permeation: Level ≤ 6 for the permeation: Tightly sealed safety glasses. ECTION 9: Physical and chemical propertiesECTION 9: Physical and chemical propertiesI Information on basic physical and chemical properties eneral Informationhysical statefolour:hell:nell:nell:nell:mamabilitynot detefoling point or initial boiling point and boilingngeNot deteformabilitynower:Not deteper:Not deteformation:17 °C	
Provide mixture of chemicals mentioned below the peri- dermeation according to EN 374 Part 3: Level 6).alue for the permeation: Level ≤ 6 bre/face protection Tightly sealed safety glasses.ECTION 9: Physical and chemical propertiesECTION 9: Physical and chemical propertiesInformation on basic physical and chemical propertieseneral InformationMot deteAccordiaA	facturer of the protective gloves and has to
Permeation according to EN 374 Part 3: Level 6).alue for the permeation: Level ≤ 6 be/face protection Tightly sealed safety glasses.ECTION 9: Physical and chemical propertiesECTION 9: Physical and chemical propertiesInformation on basic physical and chemical propertiesInformation on basic physical and chemical propertieseneral Informationhysical statefolour:Accordiaholour:Accordiaholour:Accordiaholour threshold:Not detebiling point or initial boiling point and boilingngeNot detehower:Not detepoper:Not deteash point:17 °C	
alue for the permeation: Level ≤ 6 be/face protection Tightly sealed safety glasses.ECTION 9: Physical and chemical propertiesInformation on basic physical and chemical propertieseneral Informationhysical stateFluidolour:Accordianell:Recognidour threshold:Not deteoling point or initial boiling point and boilingngeNot detelammabilityHighly fower:Not deteoper:Not deteash point:17 °C	tration time has to be at least 480 minut
pe/face protection Tightly sealed safety glasses. ECTION 9: Physical and chemical properties 1 Information on basic physical and chemical properties eneral Information hysical state Fluid olour: Accordination hysical state Fluid olour: Accordination hysical state Fluid olour: Accordination hysical state Not determination hysical state Not determination olour: Not determination hysical state Not determination hysic	
ECTION 9: Physical and chemical properties 1 Information on basic physical and chemical properties eneral Information hysical state Fluid olour: Accordination hysical state Fluid olour: Accordination hysical state Fluid olour: Accordination hysical state Not determination hysical state Not determination olour: Not determination hysical state Not determination hysical	
1 Information on basic physical and chemical properties eneral Information hysical state Fluid blour: Accordine nell: Recognit dour threshold: Not deteen biling point or initial boiling point and boiling Not deteen nge Not deteen hysical state Not deteen biling point or initial boiling point and boiling Not deteen hysical state 17 °C	
1 Information on basic physical and chemical properties eneral Information hysical state Fluid blour: Accordine nell: Recognit dour threshold: Not deteen biling point or initial boiling point and boiling Not deteen nge Not deteen hysical state Not deteen biling point or initial boiling point and boiling Not deteen hysical state 17 °C	
1 Information on basic physical and chemical properties eneral Information hysical state Fluid blour: Accordi. nell: Recogni dour threshold: Not dete biling point or initial boiling point and boiling Not dete nge Not dete ammability Highly f ower: Not dete poper: Not dete ash point: 17 °C	
eneral Informationhysical stateFluidblour:Accordi.nell:Recognidour threshold:Not deteelting point/freezing point:Not detebiling point or initial boiling point and boilingNot detengeNot deteammabilityHighly fower:Not detepoper:Not deteash point:17 °C	
hysical stateFluidblour:Accordiablour:Accordiamell:Recogniadour threshold:Not deteelting point/freezing point:Not detebiling point or initial boiling point and boilingNot detemgeNot detelammabilityHighly fpower:Not detepoper:Not detelash point:17 °C	
Jolour:Accordianell:Recogninell:Recognidour threshold:Not deteroling point/freezing point:Not deterpiling point or initial boiling point and boilingNot deterngeNot deterammabilityHighly fower:Not deteropper:Not deterash point:17 °C	
mell:Recognitdour threshold:Not detedour threshold:Not deteelting point/freezing point:Not detepoiling point or initial boiling point and boilingNot detengeNot dete'ammabilityHighly fpower:Not detepper:Not deteash point:17 °C	
dour threshold: Not deterview of the shold in the shold i	g to product specification
delting point/freezing point:Not determinationpiling point or initial boiling point and boilingNot determinationpageNot determinationlammabilityHighly fpower:Not determinationpoper:Not determinationash point:17 °C	
biling point or initial boiling point and boiling nge Not deter lammability Highly f ower: Not deter pper: Not deter ash point: 17 °C	
ngeNot detelammabilityHighly flower:Not deteoper:Not deteash point:17 °C	nined
ammabilityHighly fower:Not deteoper:Not deteash point:17 °C	
ower:Not deteopper:Not detelash point:17 °C	
pper: Not dete lash point: 17 °C	
lash point: 17 °C	
1	nined.
composition temperature: Not dete	_
1 1	
A Not dete	nined.
scosity:	
nematic viscosity Not dete	nined
namic: Not dete	
olubility	
	nined.
urtition coefficient n-octanol/water (log value) Not dete	nined. ble or difficult to mix
	nined. ble or difficult to mix

Printing date 12.09.2023

Version number 2 (replaces version 1)

Revision: 12.09.2023

Product name Stain Sedona Red

	(Contd. of page
Steam pressure:	Not determined.
Density and/or relative density	
· Density at 20 °C	0.9 g/cm^3
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of heal	th and
environment, and on safety.	
Self-inflammability:	Product is not selfigniting.
• Explosive properties:	Product is not explosive. However, formation of
	explosive air/steam mixtures is possible.
Change in condition	· ·
· Evaporation rate	Not determined.
Information with regard to physical hazard	classes
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
• Oxidising gases	Void
Gases under pressure	Void
· Flammable liquids	Highly flammable liquid and vapour.
· Flammable solids	Void
Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flamm	able
gases in contact with water	Void
• Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

64-17-5 et	hanol	
Oral	LD50	7,060 mg/kg (rat)
Inhalative	LC50/4 h	20,000 mg/l (rat)
		(Contd. on page 6)

List II

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.09.2023

Version number 2 (replaces version 1)

Product name Stain Sedona Red

Oral	LD50	5,135 mg/kg (rat)
Dermal	LD50	9,500 mg/kg (rat)
78-93-3 bi	utanone	
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	12,000 mg/l (rat)
Skin corre		tion Based on available data, the classification criteria are not met. Tritation Based on available data, the classification criteria are not met.

• Germ cell mutagenicity Based on available data, the classification criteria are not met.

- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity* Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards

· Endocrine disrupting properties

78-93-3 butanone

SECTION 12: Ecological information

· 12.1 Toxicity

- Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

· Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 7)

Printing date 12.09.2023

×

Version number 2 (replaces version 1)

Revision: 12.09.2023

Product name Stain Sedona Red

(Contd. of page 6)

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT (vapour pressure at 50°C not more the second s
IMDG, IATA	110 kPa) PAINT
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
	2 Elammable liquida
Class Label	3 Flammable liquids. 3
14.4 Packing group	-
ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Kemler Number:	33
EMS Number: Stowage Category	F-E, <u>S-E</u> B
14.7 Maritime transport in bulk according	ng to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2 Maximum not quantity new innew packaging: 30 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1263 PAINT (VAPOUR PRESSURE AT 50°C N

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 8)

GB

 $[\]cdot$ Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

Printing date 12.09.2023

Version number 2 (replaces version 1)

Revision: 12.09.2023

(Contd. of page 7)

Product name Stain Sedona Red

· National regulations

• Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing data specification sheet: Product safety · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 • * Data compared to the previous version altered.

GB •