Revision: 12.09.2023

Tel.: +49 (0)7156/357-0

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.09.2023

Version number 2 (replaces version 1)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Product name Stain Weathered Oak
- · Article number: 11525-800204-000
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture

Paint Coating

- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: LOBA GmbH & Co. KG

Leonberger Straße 56 - 62

D-71254 Ditzingen United Kingdom:

Phi House

Southampton Science Park Southampton, SO167NS United Kingdom

Phone +442380766722

- · Informing department: service@loba.de
- · 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 2 H225 Highly flammable liquid and vapour.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

P280 Wear protective gloves / eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

(Contd. on page 2)

Printing date 12.09.2023 Version number 2 (replaces version 1) Revision: 12.09.2023

Product name Stain Weathered Oak

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of the substances listed below with harmless additions.

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43-xxxx	ethanol ◆ Flam. Liq. 2, H225; ◆ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	≥25-<50%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-211-945-0011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	25-50%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3 Reg.nr.: 01-2119457290-43-xxxx	butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	<0.5%

[•] Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact The product is not skin irritating.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents

Water with a full water jet.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Printing date 12.09.2023

Version number 2 (replaces version 1)

Product name Stain Weathered Oak

(Contd. of page 2)

Revision: 12.09.2023

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Prevent material from reaching sewage system, holes and cellars.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep containers tightly sealed.

Store in cool, dry conditions in well sealed containers.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- · Requirements to be met by storerooms and containers: Store in cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed containers.

- · Storage class 3
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

 Components with critical values that require monitoring at the workplace 	· Components with	critical va	ılues that ı	require m	onitoring	at the w	vorkplace:
--	-------------------	-------------	--------------	-----------	-----------	----------	------------

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm

Sk

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

· Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 umol/L

Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.

(Contd. on page 4)

Printing date 12.09.2023 Version number 2 (replaces version 1) Revision: 12.09.2023

Product name Stain Weathered Oak

(Contd. of page 3)

- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures Wash hands during breaks and at the end of the work.
- · Breathing equipment: Not required.
- · Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.4 mm

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level ≤ 6

· Eye/face protection Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

• Physical state Fluid

· Colour: According to product specification

Smell: Recognisable
 Odour threshold: Not determined.
 Melting point/freezing point: Not determined

· Boiling point or initial boiling point and boiling

range Not determined
Flammability Highly flammable.
Lower: Not determined.
Upper: Not determined.

· Flash point: 17 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

• Kinematic viscosity Not determined. • dynamic: Not determined.

Solubility

• Water: Not miscible or difficult to mix

• Partition coefficient n-octanol/water (log value) Not determined. • Steam pressure: Not determined.

Density and/or relative density

Density at 20 °C
 Relative density
 Vapour density
 Not determined.
 Not determined.

9.2 Other information

· Appearance:

· Form: Fluid

(Contd. on page 5)

Version number 2 (replaces version 1) Revision: 12.09.2023 Printing date 12.09.2023

Product name Stain Weathered Oak

(Contd. of page 4)

· Important information on protection of health and

environment, and on safety.

· Self-inflammability: Product is not selfigniting.

Product is not explosive. However, formation of · Explosive properties:

explosive air/steam mixtures is possible.

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Void · Explosives · Flammable gases Void · Aerosols Void Void · Oxidising gases · Gases under pressure Void

· Flammable liquids Highly flammable liquid and vapour.

· Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Void · Pyrophoric solids Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water · Oxidising liquids Void Void · Oxidising solids · Organic peroxides Void Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability

· Corrosive to metals

· Desensitised explosives

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Void

- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

values that	are relevant for classification:
hanol	
LD50	7,060 mg/kg (rat)
LC50/4 h	20,000 mg/l (rat)
8 Dipropyl	ene glycol monomethyl ether
LD50	5,135 mg/kg (rat)
LD50	9,500 mg/kg (rat)
utanone	
LD50	3,300 mg/kg (rat)
LD50	5,000 mg/kg (rabbit)
LC50/4 h	12,000 mg/l (rat)
	hanol LD50 LC50/4 h 8 Dipropyl LD50 LD50 utanone LD50 LD50

(Contd. on page 6)

Printing date 12.09.2023 Version number 2 (reg

Version number 2 (replaces version 1) Revision: 12.09.2023

Product name Stain Weathered Oak

(Contd. of page 5)

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

78-93-3 butanone

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informa	tion
· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR	1263 PAINT (vapour pressure at 50°C not more tha
	110 kPa)
· IMDG, IATA	PAINT

(Contd. on page 7)

Printing date 12.09.2023 Version number 2 (replaces version 1) Revision: 12.09.2023

Product name Stain Weathered Oak

(Contd. of page 6) · 14.3 Transport hazard class(es) · ADR, IMDG, IATA 3 Flammable liquids. · Class · Label 3 · 14.4 Packing group · ADR, IMDG, IATA II14.5 Environmental hazards: · Marine pollutant: No Warning: Flammable liquids. · 14.6 Special precautions for user · Kemler Number: 33 · EMS Number: F-E,S-E· Stowage Category · 14.7 Maritime transport in bulk according to IMO Not applicable. instruments · Transport/Additional information: · Limited quantities (LQ) 5L· Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · Transport category · Tunnel restriction code D/E· IMDG · Limited quantities (LQ) 5LCode: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml UN 1263 PAINT (VAPOUR PRESSURE AT 50°C NOT · UN "Model Regulation": MORE THAN 110 KPA), 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · National regulations
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 8)

Printing date 12.09.2023

Version number 2 (replaces version 1)

Product name Stain Weathered Oak

(Contd. of page 7)

Revision: 12.09.2023

Alteration in the context will be marked with a cross (*).

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing data specification sheet: Product safety

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

* Data compared to the previous version altered.

GB