

Finished smoothing cement

Primary care	LOBA CareCleaner (gloss preservation) LOBA FloorCare Antislip (gloss increase)
Maintenance	<u>gloss preservation</u> LOBA Cleaner (maintenance cleaning) LOBA CareCleaner (wash & wax) <u>gloss increase</u> LOBA Cleaner (maintenance cleaning) LOBA FloorCare Antislip (maintenance caring)
Stripping	LOBA CareRemover

First cleaning Depending on soiling use LOBA Cleaner or LOBA CareRemover.

Primary care

Pre-treatment

The floor must be clean and free from grease, wax residues, etc. Old care layers must be removed. So at least a maintenance cleaning procedure using LOBA Cleaner is necessary. In some cases a stripping procedure (see there) must be carried out.

Caring to preserve the gloss level

To primary care use LOBA CareCleaner diluted 1:10 with water. Apply the solution using the LOBATool Wischmop. Avoid puddle formation. Never work into the drying film. After about 30 minutes the floor can be used again. Full stressability is achieved after drying over night.

Caring to increase the gloss level

To primary care use LOBA FloorCare Antislip. Apply the care product in one layer using the LOBATool Wischwiesel. Avoid puddle formation. Never work into the drying film. After about 30 minutes the floor can be used again. Full stressability is achieved after drying over night.

Maintenance

Cleaning

Add 50-100mL LOBA Cleaner to a bucket (10L) of water and wipe the floor. The cleaning intervals are to be determined according to practical experiences.

Caring to preserve the gloss level

Depending on the care layers' condition dilute LOBA CareCleaner 1:10 to 1:200 with water. Apply this solution using the LOBATool Wischmop.

Caring

If the existing protective layer is severely worn, a maintenance caring procedure can become necessary. To do so the floor has to be cleaned. Subsequently LOBA FloorCare Antislip has to be applied again undiluted using the LOBATool Wischwiesel.

Stripping

A mechanical or manual stripping procedure becomes necessary if the floor shows strong soiling which can not be removed by common maintenance cleaning. A stripping procedure is also necessary if already 3 care layers are built up and the floor should be cared again.

A stripping procedure is carried out using LOBA CareRemover (1-2,5L to a bucket (10L) of water). Spread the cleaning solution onto the floor, allow to take effect for a short period of time and work over with a buffing machine and a green pad. On small areas also a scrubber can be used. Remove dissolved dirt before it dries again. Wipe afterwards with clean water to remove any cleaner residues.

Care instruction



Finished smoothing cement
