

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/13/2019

Reviewed on 05/13/2019

1 Identification

- **Product identifier**
- **Trade name:** LOBASOL HS 2K Impact Oil Hardener B6
- **Article number:** 10610-2-250
- **Application of the substance / the mixture** *Hardening agent/ Curing agent*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 LOBA-Wakol LLC
 2401 Whitehall Park Drive Unit 950
 Charlotte, NC 28273, USA
 Fon (800) 230-6456
 info@loba-wakol.com
- **Emergency telephone number:**
For Emergency Assistance Involving Chemicals - Call INFOTRAC US. 800-535-5053
International: INFOTRAC, Tel + 1 352 323 3500
Info you need when you call: Product Name or Manufacturer Name

2 Hazard(s) identification

- **Classification of the substance or mixture**



Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.
STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**
- **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*
- **Hazard pictograms**



- **Signal word** *Warning*
- **Hazard-determining components of labeling:**
Diisocyanatpolymer
hexamethylene diisocyanate
- **Hazard statements**
Harmful if inhaled.
Causes skin irritation.
May cause an allergic skin reaction.
May cause respiratory irritation.
- **Precautionary statements**
Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves / eye protection.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a poison center/doctor if you feel unwell.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/13/2019

Reviewed on 05/13/2019

Trade name: **LOBASOL HS 2K Impact Oil Hardener B6**

(Contd. of page 1)

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**

HEALTH	1	Health = 1
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

	Diisocyanatpolymer	50-100%
	⚠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 822-06-0 EINECS: 212-485-8	hexamethylene diisocyanate	<0.5%
	⚠ Acute Tox. 3, H331; ⚠ Resp. Sens. 1, H334; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:** Rinse opened eye for several minutes under running water.· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

-US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/13/2019

Reviewed on 05/13/2019

Trade name: **LOBASOL HS 2K Impact Oil Hardener B6**

(Contd. of page 2)

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:		
822-06-0	hexamethylene diisocyanate	0.018 ppm
· PAC-2:		
822-06-0	hexamethylene diisocyanate	0.2 ppm
· PAC-3:		
822-06-0	hexamethylene diisocyanate	3 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Storage class:** 10
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/13/2019

Reviewed on 05/13/2019

Trade name: **LOBASOL HS 2K Impact Oil Hardener B6**

(Contd. of page 3)

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

822-06-0 hexamethylene diisocyanate

REL	Long-term value: 0.035 mg/m ³ , 0.005 ppm Ceiling limit value: 0.14* mg/m ³ , 0.02* ppm *10-min
TLV BEI	Long-term value: 0.034 mg/m ³ , 0.005 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**
Protective gloves
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
Nitrile rubber, NBR
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Recommended thickness of the material: ≥ 0.4 mm
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).
Value for the permeation: Level ≤ 6
- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
Form: Fluid

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/13/2019

Reviewed on 05/13/2019

Trade name: **LOBASOL HS 2K Impact Oil Hardener B6**

(Contd. of page 4)

· Color:	Colorless
· Odor:	Recognizable
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	Undetermined.
· Flash point:	212 °C (413.6 °F)
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Lower:	Not determined.
· Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.1 g/cm ³ (9.1795 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· Dynamic at 20 °C (68 °F):	200-400 mPas
· Kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions**
 - Reacts with alcohols, amines, aqueous acids and alkalis.
 - Reacts with water.
 - Danger of bursting.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/13/2019

Reviewed on 05/13/2019

Trade name: **LOBASOL HS 2K Impact Oil Hardener B6**

(Contd. of page 5)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** No irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability:** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential:** No further relevant information available.

- **Mobility in soil:** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects:** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

After prior treatment product has to be landfilled or incinerated adhering to the regulations pertaining to the disposal of especially hazardous waste.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/13/2019

Reviewed on 05/13/2019


Trade name: **LOBASOL HS 2K Impact Oil Hardener B6**

(Contd. of page 6)

14 Transport information

· UN-Number	
· DOT, ADR, ADN, IMDG, IATA	not regulated
· UN proper shipping name	
· DOT, ADR, ADN, IMDG, IATA	not regulated
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	not regulated
· Packing group	
· DOT, ADR, IMDG, IATA	not regulated
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	not regulated

15 Regulatory information

<ul style="list-style-type: none"> · Safety, health and environmental regulations/legislation specific for the substance or mixture · TSCA (Toxic Substances Control Act): All components are on the TSCA inventory 	
· Hazardous Air Pollutants	
822-06-0	hexamethylene diisocyanate
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
<ul style="list-style-type: none"> · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms 	
	
GHS07	
<ul style="list-style-type: none"> · Signal word Warning · Hazard-determining components of labeling: Diisocyanatpolymer hexamethylene diisocyanate · Hazard statements Harmful if inhaled. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. · Precautionary statements Avoid breathing dust/fume/gas/mist/vapors/spray Wear protective gloves / eye protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing. 	

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/13/2019

Reviewed on 05/13/2019

Trade name: LOBASOL HS 2K Impact Oil Hardener B6

(Contd. of page 7)

Call a poison center/doctor if you feel unwell.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

* 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

· **Department issuing SDS:** Productmanagement.

· **Date of preparation / last revision** 05/13/2019 / 3

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**